

# probuild

REINVENTING PAINT

## Low Sheen Interior

01-810X MAR 21



**DESCRIPTION:** An acrylic based interior Wall paint. Specially formulated to provide an ultra-low sheen and super fine finish over correctly applied Probuild Level 5.

**TYPICAL USES:** Interior walls.

**PERFORMANCE:** Excellent flow properties drying to an ultra-low sheen finish. Can be cut applied by roller, Spry or Spray and back-roll application to achieve a high quality of finish.

**LIMITATIONS:** Do not apply if the air and surface temperature during application and drying is likely to fall below 10°C. Not recommended for interior wet or high humidity areas such as bathrooms, laundries and kitchens (if poorly ventilated).

**TECHNICAL DATA:**

Resin:	Acrylic
Solvent:	Water
Finish:	Ultra-low sheen (5-6% @ 60°)
Colour:	White/Pastel Colours
Touch Dry (minimum):	60 minutes @ 20°C
Recoat Time (minimum):	2 hours
Primer:	See over
Number of Coats:	2
Dry Film Thickness:	31-38 microns at 12-10 m <sup>2</sup> /litre
Wet Film Thickness:	83-100 microns at 12-10 m <sup>2</sup> /litre
Durability:	Excellent
Thinning and Clean Up:	Water
VOC:	<40 g/litre
Pot Life:	Not Applicable
Pack Size:	10 Litre

**SPREAD RATE:**

Theoretical Coverage: 10-12 m<sup>2</sup>/litre/coat.  
Coverage depends on surface profile and porosity.

**ORDER CODES:**

ProBuild Low Sheen Interior 01-810

Coating Technologies Limited, 10 Andromeda Crescent, East Tamaki, Auckland 2013, New Zealand

Phone: 0064 9 837 0897 [www.cotec.co.nz](http://www.cotec.co.nz)

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if a written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.

## ProBuild Low Sheen Interior

### **SURFACE PREPARATION:**

(Refer to "Surface Preparation and Paint Systems" for full details). To ensure a successful application all surfaces to be coated must be clean, dry and stable.

All cracks and joints need to be treated as appropriate to suit the situation. Do not expect paint to bridge moving cracks/joints successfully.

Any mould, moss, algae needs to be treated with a suitable chemical cleaner/inhibitor.

Ensure surfaces are free from oil, grease and any surface contamination. Use commercial detergent/alkali cleaner, not acid wash.

Cementitious Surfaces: If lime leaching/efflorescence is possible use LIME STOP first.

Note: Commencement of work on a surface means in general you accept that surface. If any doubt about condition etc, seek advice.

### **PLASTERBOARD ETC, NEW:**

Ensure all fixing, jointing and flushing is done to manufacturers specification. Repair any damaged areas with suitable plaster or filler. Allow to cure. All surfaces must be clean and free of dust, dirt, grease.

For best finish use Probuild L5 for Level 5 finish (sanded), or EVO EASYSAND (sanded). See data Sheets for details.

### **APPLICATION:**

Brush or roller (Wooster Pro-dooz 10-13mm nap dacron roller and premium brush). Add up to 5% Summer retarder on hot, windy days to reduce drag and keep a wet edge.

Airless spray application: Pressure 2500-full pressure psi, max. tip size 413. 100 Mesh Gun Filter

### **THINNING & CLEAN UP:**

Maximum thinning 5% water or Cotec spray thinners for spraying. Clean up in water. Use a small amount of detergent to aid clean up.

### **ENVIRONMENTAL:**

The Probuild range of products are formulated on the latest available resins to give you both high performance and also to meet low VOC (Volatile Organic Compound) levels set out in current local standards. Likewise, levels of environmentally harmful substances are either significantly reduced or eliminated. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET.