PROSPEC HS HOLDOUT SEALER

TDS05-200

DESCRIPTION	Premium quality, fast drying sealer and undercoat for interior applications. It provides high opacity, a hard-even surface for low dust, free sanding and excellent hold out for topcoats.
TYPICAL USES	As a level 4, 4.5 preparation over Interior Ceilings and Broardwall and timber when finishing with Prospec LS, LE, or MF.
PERFORMANCE	Provides an excellent spray or roller application with excellent holdout for topcoats.
LIMITATIONS	Do not apply if the air and surface temperature during application is likely to fall below 10ºC. Dry time may be impeded if the relative humidity is high.
TECHNICAL DATA	Resin: Acrylic Solvent: Water Appearance: White Colour: White Primer: Not applicable Durability: Excellent Thining and Clean Up: Water VOC: <41g/litre Vol Solids: 40 percent Touch Dry: 30 minutes @20°C Recoat Time: 2 Hours @20°C Number of Coats: 1 to 2 Theoretical Coverage: 10 m²/litre/coat Wet Film Thickness: 100 microns Dry Film Thickness: 40 microns
AVAILABLE FINISHES @60°C	**Sheen** Flat 1%
SPREAD RATE	Standard Application: 10 - m²/litre/coat Hi Build: 5 - m²/litre/coat Light Coat: 12 - m²/litre/coat Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.
PRODUCT CODES	05-200.10
APPLICATION	Spray: Airless unit Graco 395 or larger. Pressure 3,000psi, tip 415-417. 100 mesh Gun filter Roll: Wooster Pro-dooz 10mm
THINNING	Water
ENVIRONMENTAL	This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET