TRUEPREP DRYWALL SEALER

TDS05-675

DESCRIPTION	A fast drying high build sealer and undercoat for interior applications. It provides high opacity and a hard even surface for low dust, free sanding. Trueprep Drywall Sealer provides excellent hold out of subsequent topcoats.
TYPICAL USES	May be used over most prepared surfaces, including Timber, previously painted surfaces, composite boards, plaster, fibre cement, Gib® Board and wallpaper.
ENVIRONMENT	Interior
PERFORMANCE	Excellent adhesion to a variety of substrates. Excellent spray application · Free sanding to a smooth surface · Excellent hold out for topcoats
LIMITATIONS	Do not apply if the air and surface temperature during application and drying is likely to fall below 10oC. Dry time may be impeded if the relative humidity is high.
TECHNICAL DATA	Resin: Acrylic Product Type: Plasterboard Sealer Solvent: Water Appearance: White Colour: White Primer: Not applicable Durability: Excellent Thining and Clean Up: Water Pack Size: 4,10 VOC: 41 Vol Solids: 32 percent Touch Dry: 30 minutes @15°C Recoat Time: 2 Hours @15°C Number of Coats: 1 Theoretical Coverage: 10 m²/litre/coat Wet Film Thickness: 100 microns Dry Film Thickness: 32 microns
SPREAD RATE	8-12 - m²/litre/coat Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.
PRODUCT CODES	05-675.04 05-675.10
SURFACE PREPARATION	**Plasterboard-Previously Painted Good** Treat and kill any areas of mould or fungal infestation. When fully killed clean the surface with Liquid sugar soap then rinse off any residual cleaner with clean water to remove all residual chemicals. Allow to dry. Thoroughly scrape and sand to remove all loose and flaking paint. Sand remaining flaking paint to a feathered edge, taking care not to fur up the underlying plasterboard surface. Spot prime any bare substrate. Fill all cracks or holes with TRUEPREP STOP-IT FILLER, or suitable stopping compound for larger repairs. Once dry sand smooth. Pole sand P240 all remaining surfaces and dust down. Seal all repaired areas and any areas of bare substrate with the manufactures recommended sealer/ undercoat. If there are any signs of water-staining that is visible on the walls or ceilings. We would recommend to seal that entire surface with TRUEPREP MULTIPURPOSE ALKYD PRIMER UNDERCOAT or TRUEPREP MULTIPRIME. Contact to Cotec Technical if in doubt.
APPLICATION	Do not apply if the air and surface temperature during application and drying is likely to fall below 10oC. Dry time may be impeded if the relative humidity is high.
THINNING	Water

ENVIRONMENTAL	This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET

COATING TECHNOLOGIES LIMITED
10 Andromeda Crescent, East Tamaki, Auckland 2013 Ph +64 9 837 0897 www.cotec.co.nz

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.