TRUEPREP DRYWALL SEALER

TDS05-675

DESCRIPTION	A fast drying high build sealer and undercoat for interior applications. It provides high opacity and a hard even surface for low dust, free sanding. Trueprep Drywall Sealer provides excellent hold out of subsequent topcoats.
TYPICAL USES	May be used over most prepared surfaces, including Timber, previously painted surfaces, composite boards, plaster, fibre cement, Gib® Board and wallpaper.
PERFORMANCE	Excellent adhesion to a variety of substrates. Excellent spray application · Free sanding to a smooth surface · Excellent hold out for topcoats
LIMITATIONS	Do not apply if the air and surface temperature during application and drying is likely to fall below 10oC. Dry time may be impeded if the relative humidity is high.
TECHNICAL DATA	Resin: Acrylic Product Type: Plasterboard Sealer Solvent: Water Appearance: White Colour: White Primer: Not applicable Durability: Excellent Thining and Clean Up: Water Pack Size: 4,10 VOC: 41 Vol Solids: 32 percent Touch Dry: 30 minutes @15°C Recoat Time: 2 Hours @15°C Number of Coats: 1 Theoretical Coverage: 10 m^2/litre/coat Wet Film Thickness: 100 microns Dry Film Thickness: 32 microns
SPREAD RATE	8-12 - m^2/litre/coat Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.
PRODUCT CODES	05-675.04 05-675.10
APPLICATION	Do not apply if the air and surface temperature during application and drying is likely to fall below 10oC. Dry time may be impeded if the relative humidity is high.
THINNING	Water
ENVIRONMENTAL	This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET