legacy

LEGACY ULTRA FLAT

TDS01-220

DESCRIPTION	A high opacity interior acrylic flat finish for ceilings.
TYPICAL USES	Ideal for general interior ceilings (Dry areas).
ENVIRONMENT	Interior
PERFORMANCE	Excellent adhesion and very flat finish with negligible side sheen. Very even finish and excellent masking of surface imperfections from reflected light. Excellent coverage.
LIMITATIONS	Do not apply if the air and surface temperature during application and drying is likely to fall below 10°C. Not recommended for wet areas.
TECHNICAL DATA	Resin: Acrylic Co-polymer Product Type: Flat Acrylic Solvent: Water Appearance: White Colour: All Colours Primer: See over. Durability: Excellent Thining and Clean Up: Water Pack Size: 4, 10 Litre VOC: <40g/litre Vol Solids: 38 percent Touch Dry: 60 minutes @20°C Recoat Time: 2 Hours @20°C Number of Coats: 2 Theoretical Coverage: 12 m²/litre/coat Wet Film Thickness: 100 microns Dry Film Thickness: 38 microns
SPREAD RATE	10-12 - m²/litre/coat Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.
PRODUCT CODES	01-220.04 01-220.10 01-2205.10
SURFACE PREPARATION	**Plasterboard-New Unpainted** All surfaces must be clean, dirt, grease and any other surface contaminant. wipe with a damp cloth to remove dust. Avoid scuffing the paper surface substrate. Inspect the substrate prior to applying any coating system to ensure there is no contamination present and no surface defects exists. If there is either contaminants or defects are present, rectification process is required prior to any coating is applied. Allow to apply first coat of primer/ sealer and allow to fully cure. If required, apply appropriate flexible paintable sealant, to gaps between skirting boards, framing and scotia's and fill any minor defects using TRUEPREP STOP-IT.

Plasterboard-Previously Painted Good
If any areas of moss or mould infestation exist, then treat them with a form of moss & mould killer solution. In area that has signs of mould infestation, it can be removed with a wipe of concentrated moss and mould killer solution on a damp cloth.

Liquid sugar soap or similar cleaner is a good method for cleaning all contaminates of the existing substrate. The surface will need to be thoroughly cleaned down to remove any residue left.

Thoroughly scrape and sand to remove all loose and flaking paint. Sand all flaking paint to a feathered edge. This will help provide a good key for painting.

Fill all cracks or holes with Trueprep STOP-IT filler, applied according to the manufacturer's instructions. Once dry sand smooth.

Seal all repaired areas and any areas of bare substrate with the manufactures recommended sealer/ undercoat.

If there are any signs of water-staining that is visible on the walls or ceilings. We would recommend to seal that entire surface with TRUEPREP MULTIPURPOSE ALKYD PRIMER UNDERCOAT which has excellent stain blocking properties. Refer to TDS for all manufactures recommendation.

APPLICATION

For most surfaces apply 1 or 2 coats of TRUEPREP EASYSAND or DRYWALL SEALER primer, in accordance with its data sheet. For premium finish 2 coats of TRUEPREP EASYSAND or 1 coat of DRYWALL SEALER applied at 6-8sqM/l, will result in a better-quality finish overall. Round head pole sand to an acceptable uniform surface, with #180-220 grit sandpaper.

Brush or roller: A Wooster Pro-Dooz sleeve (with a 10 mm nap) roller is preferred. Stir paint well before use. Recommend two coats to achieve maximum coverage. Allow 2 hours between coats.
Spray: 513-515 Tip.

THINNING

Do not thin. Clean up in water. Use a small amount of detergent to aid clean up.

ENVIRONMENTAL

This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET

COATING TECHNOLOGIES LIMITED
10 Andromeda Crescent, East Tamaki, Auckland 2013 Ph +64 9 837 0897 www.cotec.co.nz

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.