PROSPEC CP4 CEILING PAINT

TDS01-200

DESCRIPTION	Acrylic interior flat that has zero light reflectance that creates improved hiding on ceilings where a dead flat finish is required, it provides spatter free application and provides flat Level 4 finish.
TYPICAL USES	Interior Ceilings
PERFORMANCE	Excellent coverage and opacity · Easy to apply · Dries to an even dead flat Level 4 finish
LIMITATIONS	Do not apply if the air and surface temperature during application and drying is likely to fall below 10ºC. Not recommended for interior wet or high humidity areas such as bathrooms, laundries and kitchens (if poorly ventilated).
TECHNICAL DATA	Resin: Acrylic Solvent: Water Appearance: White Colour: White and Pastel Primer: See over. Durability: Good Thining and Clean Up: Water VOC: <40 g/litre Vol Solids: 38 percent Touch Dry: 30 minutes @15°C Recoat Time: 2 Hours @20°C Number of Coats: 2 Theoretical Coverage: 12 m²/litre/coat Wet Film Thickness: 100 microns Dry Film Thickness: 38 microns
SPREAD RATE	10-12 - m²/litre/coat Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.
PRODUCT CODES	01-200.10
SURFACE PREPARATION	**Plasterboard-New Unpainted** All surfaces must be clean, dirt, grease and any other surface contaminant. wipe with a damp cloth to remove dust. Avoid scuffing the paper surface substrate. Inspect the substrate prior to applying any coating system to ensure there is no contamination present and no surface defects exists. If there is either contaminants or defects are present, rectification process is required prior to any coating is applied. Allow to apply first coat of primer/ sealer and allow to fully cure. If required, apply appropriate flexible paintable sealant, to gaps between skirting boards, framing and scotia's and fill any minor defects using TRUEPREP STOP-IT.
APPLICATION	Brush or roller (Wooster Pro-dooz 10-13mm nap dacron roller and premium brush). Add up to 5% Summer retarder on hot, windy days to reduce drag and keep a wet edge. Airless spray application: Use Probuild 5 Level 5 Finish Silver or Gold package.
THINNING	Water
ENVIRONMENTAL	This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET