PROSPEC LS INTERIOR LOW SHEEN

TDS01-810

DESCRIPTION	An acrylic based interior Wall paint. Formulated to dry to an attractive low sheen finish over correctly prepared drywall over coated with Prospec HS or L5.
TYPICAL USES	• Interior walls. • Block and brickwork • Concrete and plaster • Fibre and particle board • Fibre cement • Paper faced plasterboard • Timber • Wallpaper • Wallboards
PERFORMANCE	Excellent cutting and rolling properties to provide good coverage in all off white and pastel colours. Excellent Burnish and stain resistance.
LIMITATIONS	areas such as bathrooms, laundries and kitchens (if poorly ventilated). Use Cotec Aquatec WB Enamel or Aquatec PU.
TECHNICAL DATA	Resin: Acrylic Solvent: Water Appearance: White Colour: White and Pastel Primer: See over. Durability: Excellent Thining and Clean Up: Water Pack Size: 10 Litre VOC: <40 g/litre Vol Solids: 38 percent Touch Dry: 2 hours @15°C RH <70% Recoat Time: 2 Hours @20°C Number of Coats: 2 Theoretical Coverage: 10 m²/litre/coat Wet Film Thickness: 100 microns Dry Film Thickness: 38 microns
SPREAD RATE	10-12 - m²/litre/coat Practical spreading rates will vary depending on such factors as application method, ambient conditions and surface porosity and roughness.
PRODUCT CODES	01-880.04
SURFACE PREPARATION	**Plasterboard-New Unpainted** All surfaces must be clean, dirt, grease and any other surface contaminant. wipe with a damp cloth to remove dust. Avoid scuffing the paper surface substrate. Inspect the substrate prior to applying any coating system to ensure there is no contamination present and no surface defects exists. If there is either contaminants or defects are present, rectification process is required prior to any coating is applied. Allow to apply first coat of primer/ sealer and allow to fully cure. If required, apply appropriate flexible paintable sealant, to gaps between skirting boards, framing and scotia's and fill any minor defects using TRUEPREP STOP-IT.
APPLICATION	Brush or roller (Wooster Pro-dooz 10-13mm nap dacron roller and premium brush). Add up to 5% Cotec Summer Retarder on hot, windy days to reduce drag and keep a wet edge. Airless spray application: Pressure 2500-full pressure psi, max. tip size 413. 100 Mesh Gun Filter
THINNING	Water

ENVIRONMENTAL	This formulation uses the latest technology with low toxicity, ensuring environmental issues are not compromised. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection. Refer to the MATERIAL SAFETY DATA SHEET

COATING TECHNOLOGIES LIMITED
10 Andromeda Crescent, East Tamaki, Auckland 2013 Ph +64 9 837 0897 www.cotec.co.nz

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from the date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.