



PS-E015 LANE MARKING POOLS WITH EPOTEC NT

<u>Please note all lane markings must be decided with your client. This document's purpose is to provide information and not specific direction.</u>

Guide for Lane marking as below:

The **lane markings** on the floor of the pool are a dark colour and marked in the centre of each lane. The width of the marking is 0.2m-0.3m for all pools. The length for 50m pools is 46m and 21m for 25m pools. Each lane line ends 2m from the end wall of the pool with a distinctive cross line 1m long and of the same width as the lane line.

Lane marking:

- 1. Before starting to prepare the pool surface (Removing/abrading existing coatings) Measure and document lane markings if they are to be re-instated.
- 2. It is always a good idea to take some photos too for future reference.
- 3. Application:
 - a. Can be done after the last coat is cured (Dry to walk and work on) Important to apply within 72 hours of last coat being fully applied.
 - b. Use premium quality masking tape to set out the areas to be painted (Recommend Washi# 4 or 6 needs to have conformity, sharp lines, due resistance and prevent paint seepage)
 - c. Ensure tape is firmly pressed to Epoxy before applying.
 - d. Apply Black, Royal Blue, or White with a quality brush and/or Wooster Pro-dooz 10-13mm nap mini sleeve (Available in 110 & 165mm).
 - e. Apply at 20m²/5kg/coat pack of Epotec NT.
 - i. 3 coats should be applied for maximum life, particularly in shallow areas with foot contact or exposure to pool implements.

Mixing:

If mixing a full 5Kg kit is too much material, with care smaller amounts can be mixed in a clean round plastic container in the same manner as below:

- Weigh out (not by volume) in the ratio of 4 parts resin to 1-part hardener. E.g. 800 gm Resin,
 200 gms Hardener. This will cover approx. 4m²/coat. Use kitchen scales to weigh out.
- Mix well and use immediately.
- DO NOT guess by volume but weigh out amounts.
- Incorrect ratios will result in brown staining or uncured EPOTEC.

cotecAPPLICATION GUIDE




Material guide:

		Pool length	Lane length	Width 200mm	Width 300mm	
Length		50	46	0.2	0.3	
m² per lane				9.2	13.8	
Lines to paint	8			73.6	110.4	
20m²/l/coat x 3				11	17	Kg Epotec
20111-71/COAL X 3				11	17	NT
Length		25	21	0.2	0.3	
m² per lane				4.2	6.3	
Lines to paint	8			33.6	50.4	
20m²/l/coat x 3				5	8	Kg Epotec NT
Excludes Wall markings						

Tools:

- Line marking string.
- Liquid chalk Markers
- Craft Knife
- Laser Guide
- Measuring Tape
- Grid note pad/pen.
- #4 or 6 Washi Tape 25 & 48mm
- Scales
- Wooster Pro-dooz 10-13mm nap mini sleeve (Available in 110 & 165mm).
- Brushes

cotec APPLICATION GUIDE






cotecAPPLICATION GUIDE



Markings below Federation International de Natation (FINA), as an example only.

Pool Lane Floor & Wall Details



Contact Coating Technologies technical for any clarification before proceeding.